

For Thread Size	DIN 125			BS 4320		Table 1		BS 4320	Table 2	DIN 9021		
	Sizes (mm)					Form A	Form B	Form C				
	ID	OD	Thick	ID	OD	Thick	Thick	OD	Thick	ID	OD	Thick
M1.6	1.7 - 1.84	3.7 - 4	0.25 - 0.35	1.7 - 1.85	3.7 - 4	0.2 - 0.4	-	-	-	-	-	-
M2.0	2.2 - 2.34	4.7 - 5	0.25 - 0.35	2.2 - 2.35	4.7 - 5	0.2 - 0.4	-	-	-	-	-	-
M2.5	2.7 - 2.84	5.7 - 6	0.45 - 0.55	2.7 - 2.85	6.2 - 6.5	0.4 - 0.6	-	-	-	2.7 - 2.84	7.64 - 8	0.7 - 0.9
M3.0	3.2 - 3.38	6.64 - 7	0.45 - 0.55	3.2 - 3.4	6.7 - 7	0.4 - 0.6	-	-	-	3.2 - 3.38	8.64 - 9	0.7 - 0.9
M3.5	3.7 - 3.88	7.64 - 8	0.45 - 0.55	3.7 - 3.9	6.7 - 7	0.4 - 0.6	-	-	-	3.7 - 3.88	10.57 - 11	0.7 - 0.9
M4.0	4.3 - 4.48	8.64 - 9	0.7 - 0.9	4.3 - 4.5	8.7 - 9	0.7 - 0.9	-	9.7 - 10	0.7 - 0.9	4.3 - 4.48	11.57 - 12	0.9 - 1.1
M5	5.3 - 5.48	9.64 - 10	0.9 - 1.10	5.3 - 5.5	9.7 - 10	0.9 - 1	-	12.1 - 12.5	0.9 - 1.1	5.3 - 5.48	14.57 - 15	1 - 1.4
M6	6.4 - 6.62	11.57 - 12	1.4 - 1.8	6.4 - 6.7	12.1 - 12.5	1.4 - 1.8	0.7 - 0.9	13.6 - 14	1.4 - 1.8	6.4 - 6.62	17.57 - 18	1.4 - 1.8
M8	8.4 - 8.62	15.57 - 16	1.4 - 1.8	8.4 - 8.7	16.6 - 17	1.4 - 1.8	0.9 - 1	20.5 - 21	1.4 - 1.8	8.4 - 8.62	23.48 - 24	1.8 - 2.2
M10	10.5 - 10.77	19.48 - 20	1.8 - 2.2	10.5 - 10.9	20.5 - 21	1.8 - 2.2	1.05 - 1.045	23.5 - 24	1.8 - 2.2	10.5 - 10.77	29.48 - 30	2.3 - 2.7
M12	13 - 13.27	23.48 - 24	2.3 - 2.7	13 - 13.4	23.5 - 24	2.3 - 2.7	1.4 - 1.8	27.5 - 28	2.3 - 2.7	13 - 13.27	36.38 - 37	2.7 - 3.3
M14	15 - 15.27	27.48 - 28	2.3 - 2.7	15 - 15.4	27.5 - 28	2.3 - 2.7	1.4 - 1.8	29.5 - 30	2.3 - 2.7	15 - 15.27	43.38 - 44	2.7 - 3.3
M16	17 - 17.27	29.48 - 30	2.7 - 3.3	17 - 17.4	29.5 - 30	2.7 - 3.3	1.8 - 2.2	33.2 - 34	2.7 - 3.3	17 - 17.27	49.38 - 50	2.7 - 3.3
M18	19 - 19.33	33.38 - 34	2.7 - 3.3	19 - 19.5	33.2 - 34	2.7 - 3.3	1.8 - 2.2	36.2 - 37	2.7 - 3.3	20 - 20.52	54.1 - 56	3.4 - 4.6
M20	21 - 21.33	36.38 - 37	2.7 - 3.3	21 - 21.5	36.2 - 37	2.7 - 3.3	1.8 - 2.2	38.2 - 39	2.7 - 3.3	22 - 22.52	58.1 - 60	3.4 - 4.6
M22	23 - 23.33	38.38 - 39	2.7 - 3.3	23 - 23.5	38.2 - 39	2.7 - 3.3	1.8 - 2.2	43.2 - 44	2.7 - 3.3	-	-	-
M24	25 - 25.33	43.38 - 44	3.7 - 4.3	25 - 25.5	43.2 - 44	3.7 - 4.3	2.3 - 2.7	49.2 - 50	3.7 - 4.3	26.84 - 26	70.1 - 72	4 - 6
M27	28 - 28.33	49.38 - 50	3.7 - 4.3	28 - 28.5	49.2 - 50	3.7 - 4.3	2.3 - 2.7	55 - 56	3.7 - 4.3	-	-	-
M30	31 - 31.39	55.26 - 56	3.7 - 4.3	21 - 31.6	55 - 56	3.7 - 4.3	2.3 - 2.7	59 - 60	3.7 - 4.3	33 - 34	89.8 - 92	5 - 7
M33	34 - 34.62	58.8 - 60	4.4 - 5.6	34 - 34.6	59 - 60	1.4 - 5.6	2.7 - 3.3	65 - 66	4.4 - 5.6	-	-	-
M36	37 - 37.62	64.8 - 66	4.4 - 5.6	37 - 37.6	65 - 66	4.4 - 5.6	2.7 - 3.3	71 - 72	4.4 - 5.6	39 - 40	107.8 - 110	6.8 - 9.2
M39	40 - 40.62	70.08 - 72	5.4 - 6.6	40 - 40.6	71 - 72	5.4 - 6.6	2.7 - 3.3	76 - 77	5.4 - 6.6	-	-	-
M42	43 - 43.62	76.8 - 78	6 - 8	-	-	-	-	-	-	-	-	-
M48	50 - 50.62	90.6 - 92	7 - 9	-	-	-	-	-	-	-	-	-

For more information, contact us:

ZENIA INTERNATIONAL Backside Avon Cycles, Sua Road, Industrial Area- C Ludhiana-141014 Punjab (India)

Mob: +9198550-23324, +9198555-53324 Tel: 161-5053324

www.zenialntl.com